


ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A1

Owner of the Declaration	Fletco Carpets A/S
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-FLE-20190014-CCC1-EN
Issue date	13.02.2019
Valid to	12.08.2024

**Woven TEXTiles, total pile material max. 700 g/m² PA 6.6
Fletco Carpets**

www.ibu-epd.com | <https://epd-online.com>



General Information

Fletco Carpets

Programme holder

IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Declaration number

EPD-FLE-20190014-CCC1-EN

This declaration is based on the product category rules:

Floor coverings, 01.08.2021
(PCR checked and approved by the SVR)

Issue date

13.02.2019

Valid to

12.08.2024



Dipl.-Ing. Hans Peters
(Chairman of Institut Bauen und Umwelt e.V.)



Florian Pronold
(Managing Director Institut Bauen und Umwelt e.V.)

Woven TEXTiles, total pile material max. 700 g/m² PA 6.6

Owner of the declaration

Fletco Carpets A/S
Mads Clausens Vej 2
7441 Bording
Denmark

Declared product / declared unit

1 m² woven TEXTile carpet having a pile material of PA 6.6

Scope:

The manufacturer declaration applies to a group of similar products with a maximum total pile weight of 700 g/m².
The carpet is woven at the Fletco manufacturing site Bording, Denmark.
Dyeing and backing of the carpet is carried out externally.

LCA results for product groups having a lower total pile weight can be taken from the corresponding tables of the annex or can be calculated by using equation 1 given in the annex (see annex chapter: 'General Information on the annex').

The declaration is only valid in conjunction with a valid GUT-/PRODIS/ license of the product.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A1. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard EN 15804 serves as the core PCR	
Independent verification of the declaration and data according to ISO 14025:2011	
<input type="checkbox"/>	internally
<input checked="" type="checkbox"/>	externally



Angela Schindler,
(Independent verifier)

Product

Product description/Product definition

Flat woven carpet tiles having a pile material of polyamide 6.6 (PA 6.6) and a TEXtile backing.

The declaration applies to a group of products with a maximum total pile weight of 700 g/m². The LCA results are calculated for products with the maximum total pile weight.

LCA results for product groups having a lower total pile weight can be taken from the corresponding tables of the annex.

These result tables refer to categories of total pile weights in steps of 100 g/m². The LCA results always refer to the highest total pile weight of the corresponding pile weight category.

Results for similar products with any other total pile weight can be calculated by using equation 1 given in the annex (see annex chapter: 'General Information on the annex').

For the placing on the market of the product in the European Union/European Free Trade Association (EU/EFTA) (with the exception of Switzerland) Regulation (EU) No. 305/2011 /CPR/ applies.

The Declaration of Performance of the products taking into consideration /EN 14041/ and the CE-marking of the products can be found on the manufacturer's technical information section.

Application

According to the use class as defined in /EN 1307/ the products can be used in all professional area which require class 33 or less.



Technical Data

Name	Value	Unit
Product Form	Tiles of several dimensions	-
Type of manufacture	Flat woven	-
Yarn type	Polyamide 6.6	-
Secondary backing	TEXtile backing with recycled content	-
Total pile weight	Max. 700	g/m ²
Total carpet weight	Max. 3950	g/m ²

LCA: Calculation rules

Declared Unit

Name	Value	Unit
Declared unit	1	m ²
Conversion factor to 1 kg	0.25	-
Mass reference	3.95	kg/m ²

The declared unit refers to 1 m² produced textile floor covering. Output of module A5 'Assembly' is 1 m² installed textile floor covering.

Additional product properties in accordance with /EN 1307/ and performance data of the product in accordance with the Declaration of Performance with respect to its Essential Characteristics according to /EN 14041/ can be found on the Product Information System /PRODIS/ using the /PRODIS/ registration number of the product (www.pro-dis.info) or on the manufacturer's technical information section (www.fletco.eu)

Base materials/Ancillary materials

Name	Value	Unit
Polyamide 6.6	17.7	%
Polyethyleneterephthalate (PET)	19.2	%
Mineral filler	39.0	%
Aluminium hydroxide	2.2	%
Ethyl vinyl acetate (EVA)	16.7	%
Polymer dispersion (dry substance)	4.5	%
Glass fibre	0.4	%
Additives	0.3	%

The products are registered in the GUT-/PRODIS/ Information System. The /PRODIS/ system ensures the compliance with limitations of various chemicals and Volatile Organic Compound (VOC) emissions and a ban on use of all substances that are listed as 'Substances of Very High Concern' (SVHC) under /REACH/.

This product contains substances listed in the candidate list (27.06.2018) exceeding 0.1 percentage by mass: no

Reference service life

A calculation of the reference service life according to /ISO 15686/ is not possible.

The service life of textile floor coverings strongly depends on the correct installation taking into account the declared use classification and the adherence to cleaning and maintenance instructions.

A minimum service life of 10 years can be assumed, technical service life can be considerably longer.

System boundary

Type of EPD: Cradle-to-grave

System boundaries of modules A, B, C, D:

Modules C3, C4 and D are indicated separately for three end-of-life scenarios:

- 1 - landfill disposal
- 2 - municipal waste incineration
- 3 - recovery in a cement plant

A1-A3 Production:

Energy supply and production of the basic material, processing of secondary material, auxiliary material, transport of the material to the manufacturing site, emissions, waste water treatment, packaging material and waste processing up to the

landfill disposal of residual waste (except radioactive waste). Benefits for generated electricity and steam due to the incineration of production waste are aggregated.

A4 Transport:

Transport of the packed textile floor covering from factory gate to the place of installation.

A5 Installation:

Installation of the textile floor covering, processing of installation waste and packaging waste up to the landfill disposal of residual waste (except radioactive waste), the production of the amount of carpet that occurs as installation waste including its transport to the place of installation. Generated electricity and steam due to the incineration of waste are listed in the result table as exported energy. Preparing of the floor and auxiliary materials (adhesives, fixing agents, PET connectors) are beyond the system boundaries and not taken into account.

B1 Use:

Indoor emissions during the use stage. After the first year, no product related Volatile Organic Compound (VOC) emissions are relevant due to known VOC decay curves of the product.

B2 Maintenance:

Cleaning of the textile floor covering for a period of 1 year: Vacuum cleaning – electricity supply
Wet cleaning – electricity, water consumption, production of the cleaning agent, waste water treatment.

The declared values in this module have to be multiplied by the assumed service life of the floor covering in the building in question (see annex, chapter 'General information on use stage').

B3 - B7:

The modules are not relevant and therefore not declared.

C1 De-construction:

The floor covering is de-constructed manually and no additional environmental impact is caused.

C2 Transport:

Transport of the carpet waste to a landfill, to the municipal waste incineration plant (MWI) or to the waste collection facility for recycling.

C3 Waste processing:

C3-1: Landfill disposal needs no waste processing.

C3-2: Impact from waste incineration (plant with $R1 > 0.6$), generated electricity and steam are listed in the result table as exported energy.

C3-3: Collection of the carpet waste, waste processing (granulating).

C4 Disposal

C4-1: Impact from landfill disposal,

C4-2: The carpet waste leaves the system in module C3-2,

C4-3: The pre-processed carpet waste leaves the system in module C3-3

D Recycling potential:

Calculated benefits result from materials exclusive secondary materials (net materials).

D-A5: Benefits for generated energy due to incineration of packaging and installation waste (incineration plant with $R1 > 0.6$),

D-1: Benefits for generated energy due to landfill disposal of carpet waste at the end-of-life,

D-2: Benefits for generated energy due to incineration of carpet waste at the end-of-life (incineration plant with $R1 > 0.6$),

D-3: Benefits for saved fossil energy and saved inorganic material due to recovery of the carpet in a cement plant at the end-of-life, transport from the reprocessing plant to the cement kiln.

Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's lifespan: Denmark

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account.

LCA: Scenarios and additional technical information

The following information refer to the declared modules and are the basis for calculations or can be used for further calculations. The indicated values refer to the declared functional unit of all products with a maximum total pile weight of 700 g/m².

Specific information on products having a lower total pile weight can be taken from the annex.

Transport to the construction site (A4)

Name	Value	Unit
Litres of fuel (truck, EURO 0-6 mix)	0.0066	l/100km
Transport distance	700	km
Capacity utilisation (including empty runs)	85	%

Installation in the building (A5)

Name	Value	Unit
Material loss	0.12	kg

Polyethylene packaging waste and installation waste are considered to be incinerated in a municipal waste incineration plant. Cardboard packaging waste is going to be recycled. Preparation of the floor and auxiliaries (adhesives, fixing agents, PET connectors, etc.) are not taken into account.

Maintenance (B2)

The values for cleaning refer to one m² floor covering used in commercial areas per year (see annex, chapter 'General Information on use stage').

Depending on the application based on EN ISO 10874, the technical service life recommended by the manufacturer and the anticipated strain on the floor by customers, the case-specific useful life can be established. The effects of Module B2 need to be calculated on the basis of this useful life in order to obtain the overall environmental impacts.

Name	Value	Unit
Maintenance cycle (wet cleaning)	1.5	1/year
Maintenance cycle (vacuum cleaning)	208	1/year
Water consumption (wet cleaning)	0.004	m ³
Cleaning agent (wet cleaning)	0.09	kg
Electricity consumption	0.314	kWh

Further information on cleaning and maintenance see www.fletco.eu

End of Life (C1-C4)

Three different end-of-life scenarios are declared and the results are indicated separately in module C. Each scenario is calculated as a 100% scenario.

- Scenario 1: 100% landfill disposal
- Scenario 2: 100% municipal waste incineration (MWI) with R1>0.6
- Scenario 3: 100% recycling in the cement industry

If combinations of these scenarios have to be calculated this should be done according to the following scheme:

$$\begin{aligned} \text{EOL-impact} &= x\% \text{ impact (Scenario 1)} \\ &+ y\% \text{ impact (Scenario 2)} \\ &+ z\% \text{ impact (Scenario 3)} \end{aligned}$$

Name	Value	Unit
Collected as mixed construction waste (scenario 1 and 2)	3.95	kg
Collected separately waste type (scenario 3)	3.95	kg
Landfilling (scenario 1)	3.95	kg
Energy recovery (scenario 2)	3.95	kg
Energy recovery (scenario 3)	2.3	kg
Recycling (scenario 3)	1.65	kg

Reuse, recovery and/or recycling potentials (D), relevant scenario information

Recovery or recycling potentials due to the three end-of-life scenarios (module C) are indicated separately.

Recycling in the cement industry (scenario 3):
/VDZ e.V./

The organic material of the carpet is used as secondary fuel in a cement kiln. It mainly substitutes for lignite (62.2%), hard coal (27.3%) and petrol coke (10.5%).

The inorganic material is substantially integrated in the cement clinker and substitutes for original material input.

LCA: Results

The results are valid for all declared products with a maximum total pile weight of 700 g/m². LCA results for product groups having a lower total pile weight can be taken from the corresponding tables of the annex. The LCA results always refer to the highest total pile weight of the corresponding pile weight category.

Results for similar products with any other total pile weight can be calculated by using equation 1 given in the annex (see annex chapter: 'General Information on the annex'). The declared result figures in module B2 have to be multiplied by the assumed service life (in years) of the floor covering in the building under consideration (see annex, chapter 'General Information on use stage').

Information on un-declared modules:

Modules B3 - B7 are not relevant during the service life of the carpet and are therefore not declared.

Modules C1, C3/1, C4/2 and C4/3 cause no additional impact (see "LCA: Calculation rules") and are therefore not declared. Module C2 represents the transport for scenarios 1, 2 and 3. Column D represents module D/A5.

The /CML/ characterisation factors version January 2016 are applied.

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED; MNR = MODULE NOT RELEVANT)

Product stage			Construction process stage		Use stage							End of life stage				Benefits and loads beyond the system boundaries
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	X	X	MNR	MNR	MNR	MND	MND	MND	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A1: 1 m² floorcovering

Parameter	Unit	A1-A3	A4	A5	B1	B2	C2	C3/2	C3/3	C4/1	D	D/1	D/2	D/3
GWP	kg CO ₂ eq	1.72E+01	1.66E-01	7.78E-01	0	3.17E-01	9.23E-03	7.82E+00	2.29E-02	2.81E-01	-4.15E-02	0	-1.16E+00	-3.93E-01
ODP	kg CFC11 eq	7.22E-09	4.54E-15	2.11E-10	0	1.3E-08	2.53E-16	3.12E-13	1.01E-13	7.49E-14	-8.87E-14	0	-2.46E-12	-1.58E-13
AP	kg SO ₂ eq	3.49E-02	6.82E-04	1.21E-03	0	1.24E-03	3.81E-05	5.43E-03	6.46E-05	7.58E-04	-6.89E-05	0	-1.91E-03	-1.4E-03
EP	kg PO ₄ ³ eq	4.85E-03	1.74E-04	1.87E-04	0	3.55E-04	9.73E-06	1.32E-03	6.06E-06	7.75E-04	-7.47E-06	0	-2.07E-04	-1.46E-04
POCP	kg Ethen eq	2.88E-03	-2.83E-04	8.56E-05	6.29E-05	1.56E-04	-1.58E-05	3.35E-04	4.05E-06	8.28E-05	-5.41E-06	0	-1.5E-04	-2E-04
ADPE	kg Sb eq	4.91E-05	1.38E-08	1.45E-06	0	1.1E-06	7.68E-10	3.15E-07	1.21E-08	6E-08	-1.16E-08	0	-3.21E-07	-8.93E-08
ADPF	MJ	2.91E+02	2.26E+00	8.73E+00	0	6.61E+00	1.26E-01	4.36E+00	2.42E-01	4.03E+00	-5.7E-01	0	-1.59E+01	-5.65E+01

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A1: 1 m² floorcovering

Parameter	Unit	A1-A3	A4	A5	B1	B2	C2	C3/2	C3/3	C4/1	D	D/1	D/2	D/3
PERE	MJ	3.87E+01	1.25E-01	1.16E+00	0	1.13E+00	6.98E-03	6.59E-01	1.56E-01	3.11E-01	-1.38E-01	0	-3.81E+00	-3.32E-01
PERM	MJ	0	0	0	0	0	0	0	0	0	0	0	0	0
PERT	MJ	3.87E+01	1.25E-01	1.16E+00	0	1.13E+00	6.98E-03	6.59E-01	1.56E-01	3.11E-01	-1.38E-01	0	-3.81E+00	-3.32E-01
PENRE	MJ	2.51E+02	2.27E+00	9.42E+00	0	7.88E+00	1.27E-01	6.83E+01	6.38E+01	4.18E+00	-7.22E-01	0	-2.01E+01	-5.68E+01
PENRM	MJ	6.34E+01	0	0	0	0	0	-6.34E+01	-6.34E+01	0	0	0	0	0
PENRT	MJ	3.14E+02	2.27E+00	9.42E+00	0	7.88E+00	1.27E-01	4.93E+00	4.16E-01	4.18E+00	-7.22E-01	0	-2.01E+01	-5.68E+01
SM	kg	6.01E-01	0	1.51E-02	0	0	0	0	0	0	0	0	0	1.65E+00
RSF	MJ	0	0	0	0	0	0	0	0	0	0	0	0	0
NRSF	MJ	0	0	0	0	0	0	0	0	0	0	0	0	6.34E+01
FW	m ³	8.8E-02	2.31E-04	3.46E-03	0	4.52E-03	1.29E-05	2.83E-02	2.13E-04	-1.07E-05	-1.88E-04	0	-5.2E-03	-4.62E-03

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA - WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A1: 1 m² floorcovering

Parameter	Unit	A1-A3	A4	A5	B1	B2	C2	C3/2	C3/3	C4/1	D	D/1	D/2	D/3
HWD	kg	2.31E-05	1.31E-07	6.82E-07	0	1.26E-09	7.32E-09	2.77E-08	1.95E-10	1.78E-08	-2.94E-10	0	-8.17E-09	3.2E-09
NHWD	kg	3.81E-01	1.9E-04	6.32E-02	0	8.24E-03	1.06E-05	1.74E+00	2.93E-04	3.94E+00	-3.07E-04	0	-8.52E-03	-4.26E-02
RWD	kg	9.08E-03	3.1E-06	2.73E-04	0	3.95E-04	1.73E-07	2.24E-04	6.89E-05	5.93E-05	-6.05E-05	0	-1.68E-03	-1.07E-04

CRU	kg	0	0	0	0	0	0	0	0	0	0	0	0	0
MFR	kg	9.37E-02	0	9.36E-02	0	0	0	0	1.65E+00	0	0	0	0	0
MER	kg	0	0	0	0	0	0	0	2.3E+00	0	0	0	0	0
EEE	MJ	0	0	2.22E-01	0	0	0	6.44E+00	0	0	0	0	0	0
EET	MJ	0	0	4.1E-01	0	0	0	1.19E+01	0	0	0	0	0	0

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

Disclaimer 1 – for the indicator 'Potential Human exposure efficiency relative to U235'. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators 'abiotic depletion potential for non-fossil resources', 'abiotic depletion potential for fossil resources', 'water (user) deprivation potential, deprivation-weighted water consumption', 'potential comparative toxic unit for ecosystems', 'potential comparative toxic unit for humans – cancerogenic', 'Potential comparative toxic unit for humans - not cancerogenic', 'potential soil quality index'. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high as there is limited experience with the indicator.

References

/PCR Part A/ Institut Bauen und Umwelt e.V., Berlin (pub.): Product Category Rules for Construction Products from the range of Environmental Product Declarations of Institut Bauen und Umwelt (IBU), Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Background Report, V1.7 March 2018 www.bau-umwelt.de

/PCR Part B/ Institut Bauen und Umwelt e.V., Berlin (pub.): Product Category Rules for Construction Products from the range of Environmental Product Declarations of Institut Bauen und Umwelt (IBU), Part B: Requirements on the EPD for floor coverings, V1.2, February 2018

/EN 1307/
DIN EN 1307: 2014+A1:2016: Textile floor coverings - Classification

/EN 14041/
DIN EN 14041: 2008-05: Resilient, textile and laminate floor coverings - Essential characteristics

/ISO 10874/
DIN EN ISO 10874:2012-04: Resilient, textile and laminate floor coverings - Classification

/EN 13501-1/
DIN EN 13501-1:2010-01: Fire classification of construction products and building elements - Part 1: Classification using data from reaction to fire tests

/ISO 15686/ ISO 15686: Buildings and constructed assets - Service life planning ISO 15686-1: 2011-05: Part 1: General principles and framework ISO 15686-2: 2012-05: Part 2: Service life prediction procedures ISO 15686-7: 2006-03: Part 7: Performance evaluation for feedback of service life data from

practice ISO 15686-8: 2008-06: Part 8: Reference service life and service-life estimation

/VDZ e.V./
Umweltdaten der deutschen Zementindustrie 2016

/CPR/
Construction Products Regulation, Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011

/CML/
Institute of Environmental Science (CML), University Leiden, The Netherlands

/PRODIS/
Product Information System (PRODIS) of the European Carpet Industry, Gemeinschaft umweltfreundlicher Teppichboden e.V (GUT) and European Carpet and Rug Association (ECRA), <http://www.pro-dis.info>

/REACH/
Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency (ECHA), European Union Regulation No 1907/2006, June 2017,

/GaBi database 2018/
GaBi Software-System and Database for Life Cycle Engineering, thinkstep AG, Leinfelden-Echterdingen, service pack 36, 2018

/ecoinvent 3.5/
ecoinvent, Zurich, Switzerland, Database Version 3.5, 23rd August 2018

**Publisher**

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com

**Programme holder**

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com

**Author of the Life Cycle Assessment**

Gemeinschaft umweltfreundlicher Teppichboden
(GUT) e.V.
Schönebergstraße 2
52068 Aachen
Germany

+49 (0)241 96843 410
mail@gut-ev.de
www.gut-ev.org

**Owner of the Declaration**

Fletco Carpets A/S
Mads Clausens Vej 2
7441 Bording
Denmark

+45 (0)96 60 30 00
fletco@fletco.dk
www.fletco.eu