



18

Declaration of performances
(regulation (EU) Nr. 305/2011)

DoP 150

1

Designboden

EN 16511:
2014

2

Floor covering for internal use under dry conditions

3

Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83003 Rosenheim
4018427 03 08

4

System of assessment and verification of constancy of performance

3^{*)}

5

Thickness

6,5 mm

8 mm

9,3 mm

8 mm

with cork insulation

Key properties

Reaction to fire^{*)}D_{fl} - s1C_{fl}-s1D_{fl} - s1C_{fl}-s1Content of
dangerous substances

compliant, not actively added

Emissions of VOC

≤ 0,025 mg/m³Emission of formaldehyde^{*)}

E1

Water resistance

NPD

Slip resistance

μ ≥ 0,30

Electrical behaviour

NPD

anti-
statisch

Thermal conductivity

0,133
W/mK0,143
W/mK0,147
W/mK0,125
W/mKDurability as regards reaction to
fire

NPD

DIN EN
14041:
2008

6

The performance of the product identified in (1) is in conformity with the declared performance in (5).
This declaration of performance is issued under the sole responsibility of the manufacturer (3).

Signed for and on behalf of the manufacturer

Peter Huber,
*head of production**Stephanskirchen, 15.12.2020*

^{*)} In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 2097 eco-Institut, NB 0766 eph Dresden) has/have performed type testing according to the system specified in (4).